CS F364: Design & Analysis of Algorithm

06 Greedy Algorithm Knapsack Problem

Dr. Kamlesh Tiwari
Associate Professor, Department of CSIS,
BITS Pilani, Pilani Campus, Rajasthan-333031 INDIA

Jan 20, 2025 ONLINE (Campus @ BITS-Pilani Jan-May 2025)

http://ktiwari.in/algo

Greedy Algorithm

- Strategy to solve constrained optimization problem
- Make sequence of choices [with] What looks best at the moment
- Incremental thus Efficient
- A greedy algorithm makes a **locally optimal choice** in the hope that the choice will lead to a **globally optimal** solution
- **Caution:** does NOT always yields optimal solutions
- Determine the problem has optimal substructure

Key ingredients

1. Greedy-choice property: we can assemble a globally optimal solution by making locally optimal (greedy) choices.
2. Optimal substructure: if an optimal solution to the problem contains within it optimal solutions to subproblems.

Activity Selection Problem

Activity Selection Problem:

- Consider a set $S = \{1, 2, 3, ..., n\}$ of n activities that can happen one activity at a time. Activity i takes place during interval $[s_i, f_i)$.
- Activity i and j are compatible if $[s_i, f_i)$ and $[s_j, f_j)$ do not overlap
- Select **maximum size** set of mutually comparable activities.

Consider following set of activity

i	1	2	3	4	5	6	7	8	9	10	11
s_i	1	3	0	5	3	5	6	8	8	2	12
f_i	4	5	6	7	9	9	10	11	12	14	16

- $\{3, 9, 11\}$ is a compatible activity
- $\{1, 4, 8, 11\}$ is larger compatible activity. In fact it is the largest
- Another largest compatible activity is $\{2, 4, 9, 11\}$

Activity Selection Problem

Assume that activities are in increasing order of their finishing time. If not, then sort it in $O(n \lg n)$ time.

Algorithm 1: Greedy-Activity-Selection(s, f)

```
1 n = length(s)
2 A = { 1 }
3 j = 1
4 for i = 2 to n do
5     if s_i ≥ f_j then
6         A = A ∪ { i }
7         j = i
8 return A
```

Time Complexity: $O(n \log n) + O(n) = O(n \log n)$

Activity Selection Problem



Correctness?

- Greedy choice
- Optimal sub structure

Knapsack Problem

- A thief robbing a store finds n items.
- The i^{th} item is worth p_i dollars and weighs w_i pounds. The thief wants to take as valuable a load as possible, but he can carry at most W pounds in his knapsack (consider p_i, w_i, and W as integer).
- Which items should he take?

Fractional knapsack problem:

He can take fraction of an items as well

0-1 knapsack problem:

He can either take complete items or leave

- Fractional knapsack problem can be solved with greedy but
- 0-1 knapsack problem needs Dynamic Programming

$$V(i, w) = max(V(i-1, w), V(i-1, w - w[i]) + P[i])$$

Fractional Knapsack Problem

Maximize $\sum_{i=1}^{n} p_i x_i$ subject to $\sum_{i=1}^{n} w_i x_i \leq W$ and $x_i \in [0,1]$

Algorithm 2: G-F-Knapsack($(w_1 \ldots)$, $(p_1, \ldots)$, W)

```
n = length(w)
Sort items in non decreasing order of p_i/w_i
if n = 1 then
    if (w_1 ≥ W) then return (W/w_1)
    else return (1)
if (w_1 ≥ W) then return (W/w_1,0,0,0,...)
else
    (y_2, ...) = G-F-Knapsack( (w_2, ...), (p_2, ...), W − w_1)
    return (1, y_2, ...)
```

Time Complexity: $O(n \log n) + O(n) = O(n \log n)$

0-1 knapsack problem needs DP

Let knapsack can have 50kg

3 items of wt 10, 20, 30 of price Rs 60, 100 and 120 respectively



Thank You!

Thank you very much for your attention! (Reference[1])

Queries ?

[1] Book - *Introduction to Algorithm*, By THOMAS H. CORMEN, CHARLES E. LEISERSON, RONALD L. RIVEST, CLIFFORD STEIN